

Serie K1 - K2 PORTATO



 *Dragone*

DATI TECNICI SERBATOIO K PORTATO

K mounted tank technical datas

Données techniques du réservoir porté K

Technische Angaben K Behälter Aufsattelsprünger

**SERBATOIO IN POLIETILENE A SVUOTAMENTO TOTALE
SERBATOIO LAVACIRCUITO E IGIENE OPERATORE**

*Polyethylene Tank complete emptying. Circuit cleaning tank. Handwash tank
Cuve en polyéthylène videment total. Cuve lave équipement. Cuve lave mains
PE- Behälter komplette Entleerung. Gerätwaschenwassertank, Handwassertank*

Type	Capacità serbatoio Spray tank Capacité de la cuve Flüssigkeitstank	Capacità serbatoio lavaggio circuito Circuit cleaning tank Capacité de la cuve lave équipement Gerätwaschenwassertankflüssigkeit	Capacità serbatoio operatore Handwaschtank capacity Capacité de la cuve lave mains Handwaschbehälterflüssigkeit
200 l	220 l	30 l	15 l
300 l	330 l	30 l	15 l
400 l	440 l	50 l	15 l
500 l	550 l	50 l	15 l

DATI TECNICI GRUPPO VENTOLA K

K fan group technical datas

Données techniques du ventilateur K




K Gebläse technischen Angaben

CONVOGLIATORE IN ACCIAIO INOX AISI 304 E POLIETILENE. DUE VENTILATORI A PALE REGOLABILI





*Polyethylene or stainless steel conveyor AISI 304. Two fans with adjustable blades
Convoyeur en acier inox AISI 304 ou en polyéthylène. Deux ventilateur avec pales réglables
Förderer aus inox Stahl AISI 304 oder aus PE. Zwei Gebläsen mit verstellbaren Flügeln*

Regolazione pale Blades adjustment Régulation des pales Flügelverstellung	Velocità uscita aria Airexitspeed Vitesse de l'air en sortie Luftausgangsgeschwindigkeit m/s	Portata Capacity Portée Leistung m³/h	Assorbimento di potenza Powerinput Absorption de puissance Leistungsbedarf kW
--	--	---	---





UGELLI - NOZZLES - GLICLEURS - DÜSEN: 12

20°			11.5	11270	2.3
35°			13.5	13360	3.2
45°			14.9	14740	5.4
20°			16.6	16060	4.8
35°			19.2	18840	6.9
45°			20.7	20350	9.4

UGELLI - NOZZLES - GLICLEURS - DÜSEN : 12

20°			18.2	18000	6.1
35°			23.7	23410	10.9
45°			26.2	26470	14.1
20°			23.6	25450	11.9
35°			31.3	33800	19.1
45°			34.2	37000	22.3

UGELLI - NOZZLES - GLICLEURS - DÜSEN: 14

20°			17.9	20800	8.3
35°			21.7	27550	14.9
45°			23.4	30600	16.9
20°			26.8	31200	17.7
35°			32.4	38200	26.3
45°			34.1	40000	29.8

OPTIONALS



Kit comandi su trattore- Filtro autopulente - Miscelatore polveri - Ruote
Remote control kit - Selfcleaningfilter - Premixer - Wheels
Dispositif de commande sur le tracteur - Filtre autonettoyant - Mélangeur de
poudre - Roues
Steuerungsvorrichtung im Traktor - Selbstreinigungsfiler - Staubmischer - Räder

INGOMBRI - Spaces - Mesures - Maße

Type	A (mm)	B (mm)
200	980	1400
300	980	1400
400	1140	1400
500	1140	1400

INGOMBRI GRUPPO VENTOLA

	H (mm)	
	1170	
	1250	
	1470	



**LANDBOUW - MECHANISATIEBEDRIJF
J. VAN DAM B.V.**

Janssestraat 14 4043 LH Opheusden
Postbus 15 4043 ZG Opheusden
Telefoon 0488-44 28 28
Telefax 0488-44 25 17

 **Dragone snc**

Via G. Abbate, 189 - 14054 Castagnole delle Lanze (AT) - Italy • Tel. +39 0141 876111 Fax +39 0141 8761261
e-mail: info@dragoneweb.org • www.dragoneweb.org

COPYRIGHT DRAGONE 2003



γ Krumm



LANDBOUW - MECHANISATIEBEDRIJF
R.J. VANDAM B.V.
Hamsestraat 14 4043 LH Ophoeusden
Postbus 15 4043 ZG Ophoeusden
Telefoon 0488-44 28 28
Telefax 0488-44 25 17

 Dragonne